

## GIANT FILTER HOUSING KIT

### APPLICATION

- Agriculture
- Drip Irrigation / Greenhouses
- Food Processing
- Industrial / Commercial
- R.O. Systems
- Spas & Hot Tub
- Water Wells
- Whole House Residential

### SPECIFICATION

- Threads conform to ANSI/ASME B1.20.1
- Max Pressure Rating: 90 PSI
- Temperature Rating: 39-100°F (4-38°C)
- Filter head comes with pressure relief button on inlet side
- Mounting bosses molded in head for installation with mounting bracket
- Housing kit comes complete with filter housing, 1 O-ring installed plus 1 replacement O-ring, mounting bracket & hardware, and filter bowl wrench
- Accepts industry standard cartridges (not included)
- Large capacity suitable for high flow applications

### HOUSING KIT

PART NO.	INLET/OUTLET	BOWL LENGTH	INITIAL FLOW RATE	DIMENSIONS	QUANTITY CTN	LIST PRICE-A
14FHK-GB-1007	3/4" NPT	10" Blue	7 PSI @ 12 GPM*	13.51" x 7.38"	6	107.20
14FHK-GB-1010	1" NPT	10" Blue	7 PSI @ 13 GPM*	13.51" x 7.38"	6	107.20
14FHK-GB-1015	1-1/2" NPT	10" Blue	7 PSI @ 14 GPM*	13.51" x 7.38"	6	107.20
14FHK-GC-1007	3/4" NPT	10" Clear	7 PSI @ 12 GPM*	13.51" x 7.38"	6	127.01
14FHK-GC-1010	1" NPT	10" Clear	7 PSI @ 13 GPM*	13.51" x 7.38"	6	127.01
14FHK-GC-1015	1-1/2" NPT	10" Clear	7 PSI @ 14 GPM*	13.51" x 7.38"	6	127.01
14FHK-GB-2007	3/4" NPT	20" Blue	7 PSI @ 12 GPM*	23.16" x 7.38"	6	175.84
14FHK-GB-2010	1" NPT	20" Blue	7 PSI @ 14 GPM*	23.16" x 7.38"	6	175.83
14FHK-GB-2015	1-1/2" NPT	20" Blue	7 PSI @ 15 GPM*	23.16" x 7.38"	6	175.83
14FHK-GC-2010	1" NPT	20" Clear	7 PSI @ 14 GPM*	23.16" x 7.38"	6	198.81
14FHK-GC-2015	1-1/2" NPT	20" Clear	7 PSI @ 15 GPM*	23.16" x 7.38"	6	205.29

\* Actual flow rates and pressure drop will be determined based on cartridge selection and fluid viscosity.

### ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14FHPT-GFW	Giant Filter Wrench	5.33
14FHPT-GOR	Giant Housing O-ring	3.62
14FHPT-GMB	Giant Mounting Bracket with Hardware	21.71

### REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A
14FHPT-GH-07	Giant Filter Head - 3/4" NPT	44.14
14FHPT-GH-10	Giant Filter Head - 1" NPT	44.14
14FHPT-GH-15	Giant Filter Head - 1-1/2" NPT	44.14
14FHPT-GB-10B	Giant Filter Bowl - 10" Blue	52.52
14FHPT-GB-10C	Giant Filter Bowl - 10" Clear	99.26
14FHPT-GB-20B	Giant Filter Bowl - 20" Blue	75.25
14FHPT-GB-20C	Giant Filter Bowl - 20" Clear	169.56



## GIANT HIGH TEMPERATURE HOUSINGS

### APPLICATION

- Alcohols / Toluene / Xylene
- Gasoline
- Hot Water / Liquids
- Photographic
- Salt Water Fisheries
- Vegetable Oils

### SPECIFICATION

- Threads conform to ANSI/ASME B1.20.1
- Max Pressure Rating: 100 PSI
- Max Temperature Rating: 180°F (82°C)
- Mounting bosses molded in head for installation with mounting bracket
- Securely retained O-ring eliminates potential leaks due to misplacement
- Accepts industry standard cartridges (not included)
- Suitable for high pressure service
- Excellent alternative to stainless and carbon housings
- Durable glass-reinforced nylon construction

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW RATE PSI @ GPM	DIMENSIONS	QTY CASE	LIST PRICE-A
14H-GHT10BK-1015	1" & 1-1/2" FPT	10" Black	1 @ 20*	13.33" x 7.54"	1	765.86
14H-GHT20BK-1015	1" & 1-1/2" FPT	20" Black	1 @ 25*	23.71" x 7.54"	1	925.59

\* Actual flow rates and pressure drop will be determined based on cartridge selection and fluid viscosity.

### ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14A-GFW-01	Giant universal black plastic filter wrench	12.60
14A-GOR-01	B358 Buna-N replacement "O"-ring	2.19

